









Caratteristiche

- Con azionamento manuale e spia di segnalazione della posizione di comando.
- Idoneo per azionamento continuo.

Dati di scelta e ordinazione

		U_e V c.a.	I_e A	U_c V	U.M.	Numero di ordinazione
	Relè ausiliari 1NA 	250	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	1	5TT4 201-4
						5TT4 201-3
						5TT4 201-2
	1NA+1NC 	400	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	1	5TT4 205-4
	5TT4 205-3					
	5TT4 205-2					
	2NA 	400	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	1	5TT4 202-4
	5TT4 202-3					
	5TT4 202-2					
	4NA 	400	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	2	5TT4 204-4
						5TT4 204-3
						5TT4 204-2
	1 contatto di scambio 	250	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	1	5TT4 206-4
	5TT4 206-3					
	5TT4 206-2					
	2 contatti di scambio 	400	16	8 c.a. 12 c.a. 24 c.a. 115 c.a. 230 c.a.	1	5TT4 207-4
	5TT4 207-3					
	5TT4 207-2					
						5TT4 207-1
						5TT4 207-0